

HiVol 3000 XAD Sampler

The HiVol 3000 XAD Sampler provides a flexible platform for sampling organic compounds and monitoring basic meteorological parameters.

The XAD sampler collects a wider variety of compounds (than a PUF) on a Hydrophobic Polyaromatic resin (XAD).

The HiVol 3000 XAD unit is reliable, durable and proven sampler using volumetric flow control to maintain consistent flow and collect a truly representative sample of particulate matter.

Optional attachments allow the sampler to measure wind speed and direction which can then be used as triggers to capture other meteorological parameters.



Reliable sampling

- Volumetric flow control automatically corrected to standard reference temperature
- Industrial brushless motor (100 000 hours continuous field operation)
- Weather-proof marine quality anodised aluminium cabinet
- Automatic supply voltage monitoring and shut-down facility prevents damage to instrument

Directional sampling

- Wind direction and speed used to activate/de-activate sampler
- Fence line monitoring available with a network of samplers

Enhanced communication

- RS232 output for data collection and networking
- Filter block and instrument error alarms available to email & sms
- Total control of instrument remotely from PC
- Simple programming of sampling periods, including daily and weekly programs, with in built '1-in-X day' sampling capability

**ECOTECH**WORLD CLASS
environmental
MONITORING

Specifications

Operation:	Microprocessor controlled (internal data logging)
Pump/Motor:	Side channel blower driven by an asynchronous squirrel cage motor
Flow controller:	Variable frequency drive
Volumetric flow range:	Nominal 10-15 m ³ /hr
Vacuum capability:	325 mBar max
Flow accuracy:	Better than ± 0.2 m ³ /hr
Flow repeatability:	$\pm 5\%$ of reading
Construction:	Anodised aluminium and Stainless steel
Filter size:	100mm diameter element
Construction:	Anodised aluminium cabinet with SS fasteners
Dimensions:	380mm (W) x 380mm (D) x 1300mm (H) plus inlet
Weight:	45kg plus inlet weight
Operating voltage:	200-240V $\pm 10\%$ 50/60 Hz (optional 110-240V power converter)
Running current:	4A nominal (depending on filter loading & flow rate) Start up current no more than 4A.
Temp measurement range:	0-50°C
Barometric pressure:	600-900 mmHg ± 4 mmHg

Communications/Data logging

No. of readings:	150 (averaging period is user selectable, for example 75 hours of 30min averages)
External inputs:	1 x wind direction sensor input (10k potentiometer) 1 x wind speed sensor input (contact closure) or alternatively 1 x spare contact closure input (eg. Tipping bucket rain gauge)

Options

- Calibration plate
- Field calibration transport case
- Manometer
- WS/WD sensors
- RH Sensor
- Muffler

World Wide contact details

Ph: (+61) 1300 364 946

Fax: (+61) 1300 668 763

Email: ecotech@ecotech.com.auWebsite: www.ecotech.com

BRO0259 03-FEB-10



ISO/IEC 17025