

Airflow Transducer Model 6332 / 6332D

Features:

- Smart probe technology: easy probe replacement without recalibration of the main unit
- Selectable output options: 0 to 5 V or 4 to 20 mA

Main Unit Specifications

| Model | 6332 | 6332D |
|---------------------|---|-------|
| Display | — | ○ |
| Air Velocity Ranges | Varies by probe, See below for Probe Specifications | |
| Accuracy | +/- 3% of reading | |
| Analog Output | DC 4 to 20mA or DC 0 to 5V | |
| Power Consumption | Approx. 2.0 W | |
| Power Supply | DC 12 to 24V or AC 80 to 240V | |
| Dimensions | W3.1" x H5.0" x D1.2" | |
| Weight | 0.7 lbs (320 g) | |



6332D



6332

4-Channel Anemomaster™ Model 1570

Features:

- Simultaneous measurements of 4 channels of air velocity; easy to switch over each channel display
- Software allows real-time measurements of air velocity and airflow in 4 channels
- The Model 1570 includes data processing software, RS232C cable, power cable, and 2 pc. fuse

Main Unit Specifications





| Model | 1570 |
|---------------------|---|
| Air Velocity Ranges | Varies by probe, See below for Probe Specifications |
| Resolution | 0.01 m/s |
| Interface | RS232C |
| Analog Output | 0 to 5V |
| Power Supply | AC 85 to 265V |
| Dimensions | W10.2" x H2.8" x D7.9" |
| Weight | 5.7 lbs (2.6 kg) |



Compatible Probes

■ Air Velocity Probes (V Probes)

| Probe Specifications |  |  |  |  |
|----------------------|---|---|--|---|
| Model | 0962-00 | 0963-00 | 0965-00/-01 | 0965-09/10 |
| Probe Type | Uni-Directional | Uni-Directional | Omni-Directional | Omni-Directional |
| Air Velocity | 20 to 9840 fpm (0.10 to 50.0 m/s) | 20 to 9840 fpm (0.10 to 50.0 m/s) | 20 to 4920 fpm (0.10 to 25.0 m/s) | 20 to 9840 fpm (0.10 to 50.0 m/s) |

| Probe Specifications |  |  |  |  |
|----------------------|---|---|--|---|
| | Miniature Probe with built-in temperature compensation | | Miniature Probe with independent temperature compensation | |
| Model | 0965-03 | 0965-04 | 0965-07 | 0965-08 |
| Probe Type | Omni-Directional | Omni-Directional | Omni-Directional | Omni-Directional |
| Air Velocity | 20 to 4920 fpm (0.10 to 25.0 m/s) | 20 to 4920 fpm (0.10 to 25.0 m/s) | 20 to 4920 fpm (0.10 to 25.0 m/s) | 20 to 4920 fpm (0.10 to 25.0 m/s) |