

MAXX SP5 B

Fixed site sampler in plastic housing, especially suited for high ambient temperatures. For automatic sample extraction according to the vacuum principle. Mains operation 230V/50Hz.

Type	Fixed site sampler
Housing	Made of PE with 50 mm insulation/Styrosun/PC (GF10). Housing separated in lower part (sample compartment) and upper part (control). Each part with lockable door resp. hood. Protective hood (made of Styrosun) which can be opened for operation of the control unit and service at the dosing unit.
Thermostatic control	Self-contained, controlled cooling / heating with 4 settings, no-frost. independent of the programmable controller, Temperature in sample compartment: 4°C (adjustable from 0,0-9,9°C)
Control	Microprocessor control, Sleep-Mode (<5mA), power supply 8-16 V foil keyboard (with keys 0-9, ESC, ENT, cursor), graphical display (128*64 Pixel), back lit
Data logger	3000 entries, nonvolatile data memory; storage of sampling and malfunction data like sample extractions, bottle changes, messages, external signals. optional with I/O add-on-board expandable to 32GB
Programming	12 freely programmable user programs, with function to link programs.
Program start options	Immediately; at a certain time; by an external signal
Program stop options	End of sampling program after one program run; continuous operation or x-runs
Pause mode	Interruption of program run at any time
Overfilling protection	Adjustable from 1–999 samples/bottle
Interval setting	1 min. to 99 h 59 min. in steps of 1 minute
Pulse setting	1 to 9999 pulses/sample
Manual sample extraction	Possible at any time without interrupting the current program run
Program protection	Up to 5 years after voltage loss
Interface	Mini-USB, RS422/485, RS 232 optional: Ethernet RJ45
Communication	Optional: Modbus, connection via DP PROFIBUS Optional: LAN/WLAN via TCP/IP RJ45, with IE-Browser, memory 4-32GB SD/SDHC
Languages	Multi-language, selectable
Signal inputs	<ul style="list-style-type: none"> • 2 x analogue: 0/4-20 mA, • 8 x digital (flow, event, 1 inputs can be programmed freely) option: expandable with 4x digital, 3 inputs can be programmed freely, and 8x analogue 0- 20 mA or 0-10 V, Impulslength 60ms, switching level 7-24 V, max. working restistance 500 Ohm, max. length of signalcable 30 m
Signal outputs / status messages	<ul style="list-style-type: none"> • 8 digital outputs, 1x of them as collective malfunction message option: expandable with 8 digital, 5 are freely programmable (in total 6 messages)
Sampling method	-Vacuum system 20-350 ml Option: vacuum VAR flow-proportional system 5-250 ml Option: peristaltic pump

Single sample volume accuracy	Vacuum system: < 2,5 % or +- 3 ml Peristaltic pump: +- 5 % or +- 5 ml
Suction height	Max. 7,5 m (at 1013hPa and stagnant medium), optional 8,5 m
Pumping speed	>0,5 m/s at suction height up to at least 6 m (at 1013h Pa); pump capacity can be adjusted electronically
Suction hose	PVC, L=7,5 m, ID=10 mm. Max. hose length 30 m
Sampling modes	Time-related, flow-dependent, flow-proportional, event-related, manual sample extraction
Bottle variants	Plastic 1 x 25 L 4 x 14 L 4 x 10 L 12 x 2,9 L, 24 x 1,0 L Glass 12 x 2,0 L 24 x 1,0 L
Overall dimensions	(Hxwx d) 1.100 (1.640*) x 760 x 745 mm *) with opened top
Weight	Approx. 75 kg with composite container, higher weight when using several bottles and/or glass bottles
Power supply	230 V / 115 V / AC
Power requirement	Approx. 350VA (with cooling)
Ambient temperature	-20 – 45°C
Sample temperature	0 – 40°C
Standards	CE, Sampling according to ISO 5667-2/3-10
Wetted materials	PC, PVC, Silicone, PS, PE, EPDM (optional: metering vessel glass Duran50, sinker weight SS304)

Make: MAXX
 Type: SP5 B
 Manufacturer: MAXX Mess- und Probenahmetechnik GmbH,
 Hechinger Straße 41, D-72414 Rangendingen
 Phone +49(0)7471-98481 0, Fax +49(0)7471-98481 44
e-mail: info@maxx-gmbh.com
internet: www.maxx-gmbh.com

Subject to technical changes. *) Patent No. DE 19726550A1, DE 19726549A1 and
 VAR unit DE 10008623.3

ACOEM Ecotech
 1492 Ferntree Gully Road
 Knoxfield VIC 3180
 Melbourne Australia
 Phone:+61 3 9730 7800

SP5 B

e-mail: ecotech@acoem.com
website: www.ecotech.com